

Contact Adhesives



Conbond 2466 Contact Adhesive 2466 2466R

A high performance, high solids, low viscosity contact bond adhesive designed to offer ease of use and versatility in all sizes of laminating operations. Excellent for postforming applications. Coverage approximately 275 square feet per gallon, depending on application and porosity of materials to be bonded.

- Total solids 18.5% +/- 1.5%
- Extremely high initial and ultimate strengths
- Fast drying
- High heat resistance
- Designed for maximum ease of spraying - hot or cold
- High solids translate to greatly extended coverage and lower cost per bonded foot
- Excellent general purpose adhesion to a wide variety of surfaces
- Ideal for postforming applications
- Long "open tack" - permits flexibility in production (one hour open tack time)
- Humidity resistant and water resistant - resistant to oil, alcohol and most aliphatics

Conbond 2849M Contact Adhesive 284905

A high performance spray grade contact bond adhesive in a non-flammable solvent. C2849M offers excellent sprayability, long open time and excellent heat resistance along with the fire safety, fast dry times and VOC exemptions obtained by using a non-flammable solvent. Coverage approximately 250-300 square feet per gallon, depending on application and porosity of materials to be bonded.

- Total solids 15%
- Excellent adhesion to a wide variety of substrates
- Long "open tack" - permits flexibility in production
- Aggressive grab with excellent green strength and combinability
- Designed for ease of sprayability - wide fan, good break-up
- Excellent long-term bond performance
- High heat resistance - ideal for postforming applications
- Bonds are resistant to humidity, water, oil, alcohol and most aliphatic solvents
- Non-flammable solvent system - no flash point
- Unharmful by freezing - simply warm and use

Conbond 2725 Contact Adhesive 2725 2725R

A high performance, high solids, fast drying contact bond adhesive designed for versatility. Conbond 2725 is an excellent hand spray contact bond adhesive with superior initial spot grab and outstanding combinability. Coverage approximately 250-300 square feet per gallon, depending on application and porosity of materials to be bonded.

- Total solids 19.0% +/- 1.0%
- Excellent adhesion to a wide variety of substrates
- Fast drying with wide fan and good break-up
- Long "open tack" - permits flexibility in production
- Aggressive grab with high green strength
- Designed for maximum sprayability - hot (120° F) or cold
- High solids which gives extended coverage and lower cost per laminated foot
- Excellent long-term bond performance
- High heat resistance - ideal for postforming operations
- Bonds are resistant to humidity, water, oil and most aliphatic solvents

Conbond 773HB Contact Adhesive 773HB05

A superior, high solids, brush grade contact bond adhesive designed for industrial applications. It features fast dry, high tack, long open time and outstanding combinability. Coverage approximately 260 square feet per gallon applied at 2.5 dry grams per foot, 220 square feet per gallon applied at 3.0 dry grams per foot.

- Total solids 21.5% +/- 2.0%
- Excellent general purpose adhesion to a wide variety of substrates
- High solids and viscosity to insure adequate adhesive application
- Long "open tack" - permits flexibility in production
- Aggressive grab with high green strength
- Extremely high ultimate strength
- Excellent long-term bond performance
- Excellent heat resistance - suitable for "single edge" postforming
- Outstanding resistance to static stress
- Bonds are resistant to humidity, water, oil and most aliphatic solvents

55 Gallon Product No.	5 Gallon Product No.	Gallon Product No.	Product No.	Description
246655	246605			Conbond 2466 Contact Adhesive - Flammable, Natural
2466R55	2466R05			Conbond 2466 Contact Adhesive - Flammable, Dyed Red
272555	272505			Conbond 2725 Contact Adhesive - Flammable, Natural
2725R55	2725R05			Conbond 2725 Contact Adhesive - Flammable, Dyed Red
	284905			Conbond 2849M Contact Adhesive - Non-Flammable, Clear
	773HB05			Conbond 773HB Contact Adhesive - Flammable, Natural

Contact Adhesives



Conbond 330 Contact Adhesive C330 C330G

CONBOND 330 is a non-flammable neoprene based water-borne contact bond adhesive formulated for home and shop use. It has been formulated to retain the versatility and performance of traditional flammable and non-flammable solvent-based neoprene contact adhesives yet allows the safety and non-toxicity of using a water-borne adhesive. Suitable for use in bonding a wide variety of materials including, but not limited to, decorative laminated, particleboard, plywood, rigid plastics, leather, etc. Coverage approximately 575-675 square feet per gallon, depending on application and porosity of materials to be bonded.

- Total solids 49.0% +/- 1.5%
- Excellent adhesion to a wide variety of substrates
- High initial green strength allowing immediate machining of laminates
- Long open tack - permits flexibility in production (one hour open time)
- Excellent heat resistance
- Ease of application - brush, paint roller, spray
- Ease of clean-up - wet adhesive can be cleaned with warm soapy water
- Non-flammable - the solvent in the adhesive is water
- Complies with SCAQMD, Rule 1168
- Meets requirement for LEED® IEQ Credit 4.1: Low Emitting Materials: Adhesive & Sealants

Conbond High Strength Adhesive Spray Canister/Aerosol C690

Designed specifically for bonding high pressure laminates to various substrates, C690 is also suitable for a variety of applications in woodworking, manufactured housing, general construction, recreational vehicle, marine, furniture, textile, HVAC, upholstery and more. It can be used on many porous or non-porous surfaces where a permanent bond is required. Coverage approximately 2.5 dry grams per square foot. **MH974** canister hose and **SE200** spray gun also available.

- Quick tack
- Fast drying
- Excellent shear strength
- Low maintenance system
- Precise application control
- Good heat resistance
- Easy cleanup

Conbond "Z" Solvent-Free Postformable Contact Adhesive Z100

Z Solvent-Free Postformable Adhesive is a high-strength contact adhesive that combines high performance with regulatory compliance. As the first GREENGUARD® Indoor Air Quality Certified contact adhesive, Z offers a unique confidence in product quality, as well as worker and customer safety. Z is used to bond high pressure laminate, decorative metals and phenolic-backed veneers to a variety of popular substrates. Coverage approximately 1150 square feet per gallon, depending on application and porosity of materials to be bonded.

- Total solids 55.1%
- High bond strength: comparable to solvent-based products at similar coating weight
- High heat resistance: postformable
- High yield: 3-4 times more coverage than solvent-based adhesives
- GREENGUARD® Indoor Air Quality Certified; GREENGUARD® Children & Schools Certified
- Zero solvents • Zero flammability • Zero VOCs • Zero HAPs
- Zero methylene chloride • Zero hazardous waste
- Complies with SCAQMD, Rule 1168
- Contributes to LEED® EQ Credit 4.1: Low Emitting Materials: Adhesive & Sealants
- Contributes to LEED® EQ Credit 4.4: Low-Emitting Materials: Composite Wood & Agrifiber Products
- Contributes to LEED® EQ Credit 3.2 and LEED® ID Credit 1-1.4

Conbond Top Grip® Flammable Solvent Cleaner/Thinner ST102

ST102 is a flammable solvent cleaner/thinner for TACC flammable solvent products. It can also be used as a cleaner for over-spray and spray equipment. ST102 features quick cut action.

55 Gallon Product No.	5 Gallon Product No.	Gallon Product No.	Product No.	Description
	C33005			Conbond 330 Waterbase Contact Adhesive - Clear
	C330G05			Conbond 330 Waterbase Contact Adhesive - Green
	Z100C05			Conbond Z Solvent-Free Postformable Contact Adhesive - Clear
	Z100G05			Conbond Z Solvent-Free Postformable Contact Adhesive - Green
			C69017C	Conbond Propellant 17 oz. Aerosol Adhesive - Clear
			C69037C	Conbond Propellant 37 lb. Canister Adhesive - Clear Returnable
			C69037G	Conbond Propellant 37 lb. Canister Adhesive - Green Returnable
			C69734G	Conbond Propellant 37 lb. Canister Adhesive - Green Returnable
			MH974	Conbond Canister Hose - 18 Foot
			SE200	Conbond Prostyle Spray Gun for Canisters
	ST10205	ST10201		Conbond Top Grip Flammable Solvent Cleaner/Thinner